

IN THE SPECIFICATION:


The paragraph on page 9, lines 21-25 has been amended as follows:

21 Preferably, the unintegral turns of the fiber reinforced resinous layers wound by more than 1 (one turn) is  $N+0.5$  (N is an integer of one or more ~~than 1~~). The way of winding the prepreg efficiently allows a part in which the prepreg is wound by 0.5 turns to be anisotropic ~~efficiently~~.

The paragraph on page 10, lines 1-17 has been amended as follows:

According to the present invention, there is provided a golf club shaft having a first inclined fiber reinforced resinous layer in which reinforcing fibers are oriented at an angle of  $\alpha^\circ$  ( $0^\circ < \alpha < 90^\circ$ ) with respect to an axis of the golf club shaft and a second inclined fiber reinforced resinous layer in which reinforcing fibers are oriented at an angle of  $-\alpha^\circ$  with respect thereto and which is adjacently layered in a winding state at one portion or more of the golf club shaft, wherein a winding start position of the first inclined fiber reinforced resinous layer and a winding start position of the second inclined fiber reinforced resinous layer are spaced at  $180^\circ$  in a circumferential direction of the golf club shaft and the first inclined fiber reinforced resinous layer and the second inclined fiber reinforced resinous layer are wound

Appl. No. 09/295,273

 by  $N+0.5$  turns (N is an integer of one or more ~~than 1~~)  
respectively.

---

BEST AVAILABLE COPY